

5CP PLUNGER PUMP



SKU: 215 5CPQ6221

2,000 PSI @ 22.7 L/min
1/2" F NPT In, 3/8" F NPT Out
316 Stainless Steel

Features

- 5CP Plunger Pump
- Industrial Duty, Long Lasting, Dependable Pumps
- This triplex (three plunger rods) positive displacement, reciprocating plunger pump is constructed with 316 stainless steel manifolds, 316 stainless steel valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and O-rings.
- Cat Pumps "Q" pump models reduce sound levels by -6 dBa (decibels). With "Q" model pumps and other noise reduction measures, equipment builders can supply quiet, pleasing equipment to their customers.

Specifications

- **Maximum Flow:** 22.7 L/min
- **Maximum Pressure:** 2,000 PSI
- **Inlet:** 1/2" F NPT
- **Outlet:** 3/8" F NPT
- **Speed:** 1,400 RPM
- **Drive:** Belt, clutch, flexible coupling, and bellhousing
- **Material:** 316 Stainless Steel



Recommended Accessories

- **Inlet Filter for CAT Pumps** 225 7105.5
- **Inlet Pressure Stabilizer for CAT Pumps** 225 711500
- **Oil Drain Kit for CAT Pumps** 225 34334
- **Cat Pump Crankcase Oil ISO 68** 225 6107
- **Pulsation Dampener - Rechargeable, NBR for CAT Pumps** 225 6031
- **Stainless Steel Pop-Off Valve for CAT Pumps** 225 9961
- **Stainless Steel Pre for CAT Pumps** 225 36126
- **Stainless Steel Pressure Gauge for CAT Pumps** 225 6097
- **Stainless Steel Pressure Regulator for CAT Pumps** 225 7002.100
- **Stainless Steel Pressure Sensitive Regulating Unloader for CAT Pumps** 225 7501

