

SKU: 220 ESR 185/160-1800

**Pressure - 2320 psi**

**Flow - 185 L/min**

**Speed - 1800 RPM**



## Features

- Triplex plunger pump in line
- Pump body: aluminium alloy
- Symmetric crankcase featuring top and bottom fixing for easy right to left shaft conversion
- Head: stainless steel
- Camshaft: forged steel
- Splash lubrication
- Shaft support tapered roller bearings oversized for long duration
- Connecting rods: steel with thin-shell bearings
- Guiding piston: stainless steel
- Solid ceramic plungers
- PATENTED stainless steel
- Suction/delivery valves featuring spherical design of sealing areas
- Seals: high dependability with low-pressure lubrication and recirculation chamber
- Versions in direct drive mount or with side gearbox available in 3 gear ratios and positionable on the right or left of the pump at 0° – 45° – 90° – 135° – 180° from the horizontal plane (see drawing)

## Specifications

- **HPP Model** - ESR 185/160
- **HPP Code** - 6920 0022
- **Speed** - 1800 RPM
- **Flow** - 185 L/min
- **Pressure** - 2320 psi
- **Power** - 79 hp
- **Max Inlet Pressure** - 43.5 psi
- **Oil Capacity** - 5.65 L 80W 90
- **Oil Capacity with Gearbox** - 7.10 L 80W 90
- **Weight** - 107 kg



## Options

1. On request Stainless Steel AISI 316
  2. Flushing systems available on request on selected versions
- 

