

SPECIFICATIONS	Model	HS2.4S									
		HS-series									
		0.4kW, 1-phase									
<p>Type of Pump Submersible drainage pump for construction and foundation works, floodwater drainage, etc.</p> <p>Type of Fluid Stormwater, groundwater, wash water, and sand-carrying water</p> <p>Temperature: 0 to 40°C</p> <p>Discharge Bore & Connection 50mm, Hose Coupling</p> <p>Motor Output 0.4kW</p> <p>Power Supply Single-phase</p> <p>Starting Method Capacitor Run</p> <p>Motor Continuous-duty rated, dry-type induction motor</p> <p>Insulation Class: E Degree of Protection: IP68</p> <p>No. of Poles & Speed (Synchronous Speed) 2-pole, 3000/3600min⁻¹ (50/60Hz)</p> <p>Power Supply Voltages & Rated Currents</p> <table border="0"> <tr> <td>50Hz</td> <td>60Hz</td> </tr> <tr> <td>220V – 2.7A</td> <td>110V – 5.4A</td> </tr> <tr> <td>230V – 2.6A</td> <td>220V – 2.7A</td> </tr> <tr> <td>240V – 2.6A</td> <td></td> </tr> </table> <p>Power Cable Sheath: H07RN-F Standard Length: 10m 100 to 240V supply: 1 x 3 x 1.0mm², O.D. 9.0mm</p> <p>Dry Weight (excluding cable) 11.3kg</p>	50Hz	60Hz	220V – 2.7A	110V – 5.4A	230V – 2.6A	220V – 2.7A	240V – 2.6A		<p>Impeller Vortex impeller deigned for “high-gap structure”, made of urethane rubber</p> <p>Solids Passage 50Hz – ϕ7mm 60Hz – ϕ7mm</p> <p>Agitator Sintered alloy</p> <p>Cable Entry with Anti-Wicking Block Watertight cable entry with strain-relief device. The anti-wicking block prevents water incursion due to capillary action should the power cable be damaged or the end submerged.</p> <p>Bearing Permanently lubricated, deep-groove, double-shielded C3 ball bearings</p> <p>Shaft 403 stainless steel</p> <p>Shaft Seal (Mechanical Seal) Furnished with a double-face mechanical seal located in oil chamber. Both upper and lower seal faces always run in a clean environment.</p> <p>Upper Seal Face: Ceramic + Carbon Lower Seal Face: SiC + Ceramic</p> <p>OIL LIFTER Equipped in oil chamber. It forcibly supplies lubricating oil to the mechanical seal and continues to supply the oil to the upper seal faces even if lubricant falls below the rated volume.</p> <p>Type of Lubricating Oil & Volume Turbine Oil (ISO VG32), 160ml</p> <p>Motor Protection Device A miniature thermal protector is embedded in winding of the motor. Directly cuts the motor circuit if excessive heat builds up in the motor.</p>		
50Hz	60Hz										
220V – 2.7A	110V – 5.4A										
230V – 2.6A	220V – 2.7A										
240V – 2.6A											
<p>Optional Accessory</p> <p>Male Threaded Coupling</p>											
TSURUMI MANUFACTURING CO., LTD.											